

Hill-Rom 880, 881, 882, 883, 885, 886 GPS Procedural Stretcher Spec Sheet

<u>Feature</u>	<u>Dimension</u>
Overall length	84" (213.4 cm)
Overall height – low position (without mattress)	23.5" (59.7 cm)
Overall height – high position (without mattress)	38.5" (97.8 cm)
Total hilow travel	15" (38.1 cm)
Overall width – siderails stored (For models 880, 881, 882, and 883)	28.5" (72.4 cm)
Overall width – siderails stored (For models 885 and 886)	32.5" (82.6 cm)
Overall width – siderails extended (For models 880, 881, 882, and 883)	33.5" (85.1 cm)
Overall width – siderails extended (For models 885 and 886)	37.5" (95.3 cm)
Siderail length	56.75" (144.1cm)
Clearance inside siderails (width) (For models 880, 881, 882, and 883)	28" (71.1 cm)
Clearance inside siderails (width) (For models 885 and 886)	32" (81.3 cm)
Siderail height fully up	14.5" (36.8 cm)
Siderail height intermediate	12.5" (31.8 cm)
Sleeping surface (For models 880, 881, 882, and 883)	26.25" x 78.25" (66.7 cm x 198.8 cm)
Sleeping surface (For models 885 and 886)	30" x 78.25" (76.2cm x 198.8 cm)
Mattress thickness	2" (5.1 cm), 3" (7.6 cm), or 4" (10.2 cm)
Caster wheel	8" dia x 1.5" wide (20.3 cm dia. x 3.8 cm wide)
Caster type	Polyurethane
Wheel base, center to center – length	46" (116.8 cm)
Wheel base, center to center – width	23.5" (59.7 cm)
Clearance under stretcher (without Steering Plus II option)	6.5" (16.5 cm)
Clearance under stretcher (with Steering Plus II option)	3.25" (8.3 cm)
Trendelenburg angle inclination	11°
Reverse Trendelenburg angle inclination	10°
Head section inclination – manual	90°

Hill-Rom 880, 881, 882, 883, 885, 886 GPS Procedural Stretcher Spec Sheet

Head section inclination – assisted	80°
Thigh section inclination	40°
Maximum stretcher weight (without Steering Plus II option)	288 lbs
Maximum stretcher weight (with Steering Plus II option)	303 lbs
Maximum patient weight	500 lbs
Trendelenburg gas cylinder size	450 Newtons
Head gas cylinder size	700 Newtons